

Huck® FloorTight® Tooling/Nose Assembly Selection

FloorTight®								
NOSE ASSEMBLY	FASTENER TYPE	FASTENER DIAMETER	FASTENER DIAMETER	LENGTH	RELEASE (JAWS)	COMMENTS	PNEUDRAULIC TOOL	HYDRAULIC TOOL
99-3452*	FLOOR TIGHT	-10	5/16"	STD	NSR	-----	256	2581,2583*
99-3441*	FLOOR TIGHT	-08	1/4"	STD	NSR	-----	256	2581,2583*
99-3452UK	FLOOR TIGHT	-10	5/16"	STD	NSR	-----	256	2581,2583

hfsindustrial.com

[YouTube.com/HFSIndustrial](https://www.youtube.com/HFSIndustrial)

The information contained in this publication is only for general guidance, and is not intended to create any warranty, express, implied, or statutory; all warranties are contained only in Howmet Fastening Systems' written quotations, acknowledgments, and/or purchase orders. It is recommended that the user secure specific, up-to-date data and information regarding each application and/or use of such products.

North America

Waco Operations

PO Box 8117
8001 Imperial Drive
Waco, TX 76714-8117
Tel: +1 800-388-4825
Fax: +1 800-798-4825
sales.waco@howmet.com

Kingston Operations

1 Corporate Drive
Kingston, NY 12401
Tel: +1 800-278-4825
Fax: +1 845-334-7333
sales.kingston@howmet.com